


3DX-RAY

3DX-WALK BY METAL DETECTOR



The 3DX-Walk By Metal Detector is the proven choice for cell phone, weapon and contraband detection. It provides the effectiveness, versatility and ease of use that correctional facilities need to combat contraband issues associated with gaps in traditional security systems.

Featuring highly effective ferromagnetic detection (FMDS) technology, the 3DX-Walk By Metal Detector has been designed to keep both large and small concealed contraband from escaping detection. Its features and benefits include:

2x sensitivity detection in biggest concealment areas*

Detect very small contraband items from razors to tattoo needles, often missed by alternative technologies

50% fewer nuisance alarms*

Advancements in our technology provide immunity to nearby metal doors and other stationary metal objects

Portable, full body screening for small and large size objects

Full scan of the entire body in a single walk-by (40 subjects per minute)

Versatile

Functions in vertical and horizontal positions to screen inmates and their belongings

Easy to deploy

Setup and begin screening in 10 seconds

Detection of cell phones

Detect cell phones when on or off, and anywhere on the person or internalised

Covert screening


Useful for surprise and covert screening of inmates and their belongings, including mattresses, laundry items, and commissary items

Safe & non-emitting

Does not radiate or emit, making it 100% passive and safe for all individuals including those with pacemakers or who are pregnant

Ruggedised

Designed to operate in harsh conditions and treatment, both indoors and outdoors



**measured in comparison with best performing competitive detection product*

3DX-WALK BY METAL DETECTOR

Technical Specifications

Controls

- On/Off push button
- Sensitivity control for red alert
- Audible alarm on/off control

Power Supply	Battery	12V DC 4.5Ah sealed lead acid 100/240V AC battery charger
	Charge Time	4 hours
	Battery Run Time	10-16 hours on full charge
	Charging Ports	1 on front of unit 1 on bottom of unit

Temperature Range -10°C to +50°C / +14°F to +122°F

Relative Humidity 0 - 95% NC

Weight Unit: 9kg (19.8lbs) Base: 9kg (19.8lbs)

Dimensions	Unit (WxDxH)	13.46 x 8.64 x 184.40cm (5.3" x 3.4" x 72.6")
	Base (WxDxH)	34 x 34 x 36cm (13.4" x 13.4" x 14.2")
	Wall Mount Profile	9.14cm (3.6")



72.6" / 184.4cm

5.3" / 13.46cm

www.3dx-ray.com

T. +44 (0) 1509 817400 F. +44 (0) 1509 817401 E. sales@3dx-ray.com

3DX-RAY Ltd, 16 & 18 Hayhill Industrial Estate,
Barrow upon Soar, Leicestershire, LE12 8LD, UK

An **IMAGE SCAN** company

Registered address: 16 & 18, Hayhill Industrial Estate,
Barrow upon Soar, Leicestershire, LE12 8LD, UK.
Registered in England No. 3237543.

